

**Ozone
Only
Applications**



Epoxy coated to prevent corrosion

FEATURES

- Full colour touch screen display
- Highest grade HEPA and carbon technology
- Automatic electronic flow control - maintains a constant extraction rate even as the filter blocks
- Gas and particle sensors to warn the operator
- Operate worldwide with no loss of performance

SPECIFICATIONS

| | |
|---------------------------|---------------------------|
| Voltage | 90v - 254v |
| Volume Part Number | 1704132 |
| Wattage | 1.1kW |
| Frequency | 50Hz / 60Hz |
| Cabinet Height | 1195mm |
| Cabinet Width | 528mm |
| Cabinet Depth | 465mm |
| Cabinet Weight | 70Kg |
| Sound Level | <60dBa |
| Airflow | 400m³/h |

INCLUDED AS STANDARD...

FILTERS



**Main Filter
Code**
113450

Description
HEPA/
Twin Chemical



**Pre-filter
Code**
111097

Description
F8/F9 Labyrinth



**Pre-filter
Code**
200037

Description
Chemical
Absorbant Pad

Find out more:

 www.purex.co.uk

 purex@purex.co.uk

 **+44 (0)1405 746030**

FILTER MONITOR UNIT



Code
400470

Description
Ozone FMU

The ozone FMU will detect Ozone only and no other contaminants

CONNECTION KIT

Connection kit is included see overleaf for options

OPTIONS

Connection Kits

Hose End Diameter

Hose Length

Purex Inlet Diameter

Code: 100043C

50mm


6m

80mm

Epoxy coated to prevent corrosion

Connect to 50mm diameter pipe/port or Purex valve

6.0m



Code: 120299


80mm

3m

80mm


Connect to 80mm diameter pipe/port

3.0m



If you do not see a connection kit that fits your machine or pipework, please contact Purex or your representative

Interfacing



Interfacing can remotely start the Purex machine when the connected machine starts.

Interfacing can also warn the connected machine when the Purex machine is in alarm.

Take a look through our Interfacing Guide to see our extensive range of options



Purex International Limited
QWP House, Island Drive
Capitol Park, Thorne
Doncaster, UK
DN8 5UE